

## 2-Xperience Primary Clear Acryl Audiophile turntable

- Belt driven turntable with 2-step pulley
- Stand-alone motor base
- 33/45 rpm with manual speed change
- MDF platter with felt mat & record clamp
- 9" aluminium tonearm
- Audiophile grade tonearm cable *Connect it E* included
- Available in transparent acrylic

<b>Principle</b>	Belt Drive
<b>Platter</b>	MDF
<b>Nominal speeds</b>	33/45 rpm
<b>Speed variance</b>	33: ±0,40% 45: 0,35%
<b>Wow and flutter</b>	33: ±0,19% 45: 0,17%
<b>Signal to noise</b>	-65dB
<b>Tonearm</b>	9"; aluminium
<b>Effective tonearm length</b>	9" (230mm)
<b>Overhang</b>	18mm
<b>Effective tonearm mass</b>	15g
<b>Accessories</b>	Clamp, Connect it E cable, power supply
<b>Turntable lid</b>	Included
<b>Power consumption</b>	5W max/ >0,5W standby mode
<b>Outboard power supply</b>	15V DC / 800mA, 90-264V AC, 47 – 63Hz
<b>Dimensions (W x H x D)</b>	465 x 130 x 340mm
<b>Weight</b>	6,5 kg



### Audiophile turntable with acrylic chassis and class-leading sound!

*2Xperience Primary Clear Acryl* is an ultra-stylish record player that uses advanced technology for great sound. A quiet running AC motor with a two-step pulley drives the platter's outside edge via a belt. The resonance-optimised MDF platter with screw-down record clamp runs on a low-tolerance stainless-steel axle with Teflon bearing plate in a sintered bronze bearing housing. The transparent acrylic plinth stands on three height-adjustable TPE-damped aluminium cones. An external power supply avoids potential electro-mechanical interference.

The sophisticated 9" tonearm uses an one-piece aluminium headshell & armtube and an inverted bearing design with four hardened ABEC7 spec ballraces. It's solid armbase permits accurate height adjustment of armtube and VTA (vertical tracing angle) if needed. The internal wiring consists of flexible high-purity copper from the headshell right through to the gold-plated phono sockets.

